

## **TECHNICAL SPECIFICATIONS**

**Manufacturer**                      *Sadra Naft Parsian Co.*

**Product name**                    *Blending Heavy Hydrocarbon*

### ***BLENDING HEAVY HYDROCARBON SD-60***

<b>NO</b>	<b>PROPERTY</b>	<b>UNIT</b>	<b>LIMIT</b>	<b>TEST METHOD</b>
<b>1</b>	Density @ 15 °c	g/cm <sup>3</sup>	0.820 min 0.860 max	ASTM D-1298
<b>2</b>	I.B.P	°C	150 min	ASTM D-86
<b>3</b>	Recovered@90%	°C	380 max	ASTM D-86
<b>4</b>	F.B.P	°C	390 min	ASTM D-86
<b>5</b>	Doctor Test	---	Negative	ASTM D-4952
<b>6</b>	Total Sulfur	Wt. %	0.2 max	ASTM D-4294
<b>7</b>	Flash Point	°c	60 min	ASTM D-93
<b>8</b>	Ash	Wt. %	0.01 min	ASTM D-482
<b>9</b>	Pour Point	°C	-5 min	ASTM D-97
<b>10</b>	Cetan Index	---	50 min	ASTM D-4737
<b>11</b>	Color Saybolt	---	20 max	ASTM D-156
<b>12</b>	Water & Sediment	Vol%	Trace	ASTM D-2709

**SADRA NAFT PARSIAN Co.**

No. 9, 6<sup>th</sup> floor – 31<sup>st</sup> St. – Alvand St.

Argentina Sq. Tehran, Iran.

Tel: (+98) 21 8867 1360-1, 8820 3080

Fax: (+98) 21 8820 9903

Email: [info@parsianoilgroup.com](mailto:info@parsianoilgroup.com)

[www.parsianoilgroup.com](http://www.parsianoilgroup.com)

